Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (Currently amended) A drum flap having a part-cylinder surface, which forms a first region ~~(2; 102; 302)~~, with two circle segment surfaces, which each form a second region ~~(3; 103; 303)~~, and having an externally surrounding rim ~~(4; 104; 304)~~, which is arranged substantially in two planes, projects outward and serves to bear against correspondingly designed bearing surfaces, ~~characterized in that~~ wherein the drum flap ~~(1; 101; 201; 301; 301')~~ has at least a second rim ~~(5; 105; 305)~~.

2. (Currently amended) The drum flap as claimed in claim 1, ~~characterized in that~~ wherein the second rim ~~(5)~~ is provided in the first region ~~(2)~~ of the drum flap ~~(1)~~.

3. (Currently amended) The drum flap as claimed in ~~claim 1 or 2, characterized in that~~ claim 1, wherein the second rim ~~(5)~~ is provided in the second region ~~(3)~~.

4. (Currently amended) The drum flap as claimed in ~~one of claims 1 to 3, characterized in that~~ claim 1, wherein the second rim ~~(105; 305)~~ is arranged in a plane in which a pivot axis also lies, and projects outward, the plane in which the second rim ~~(105; 305)~~ lies being arranged in an angle between the other two planes in which the first rim ~~(104; 304)~~ lies.

5. (Currently amended) The drum flap as claimed in ~~one of claims 1 to 4, characterized in that~~ claim 1, wherein the drum flap ~~(1)~~ has at least one opening in at least one segment ~~(2", 3")~~ of the first and/or second region ~~(2 or 3, respectively)~~, the segment ~~(2", 3")~~ being delimited by two adjacent rims ~~(4, 5)~~.

6. (Currently amended) The drum flap as claimed in ~~one of claims 1 to 5, characterized in that~~ claim 1, wherein a circular region ~~(7)~~, the thickness of which is designed to match the rims ~~(4, 5)~~, is provided in the region of the pivot axis.

7. (Currently amended) The drum flap as claimed in claim 1, ~~characterized in that~~ wherein the second rim ~~(105; 305)~~ runs substantially around a third region ~~(110)~~, which directly or indirectly – separated by an intermediate region ~~(340)~~ – adjoins the lateral surface in the region of the first rim ~~(104; 304)~~.

8. (Currently amended) The drum flap as claimed in claim 7, ~~characterized in that~~ wherein the third region ~~(110; 310)~~ is approximately rectangular in form.

9. (Currently amended) The drum flap as claimed in ~~claim 7 or 8, characterized in that~~ claim 7, wherein the planes in which the third region ~~(310)~~ and the intermediate region ~~(340)~~ lie are arranged at an angle not equal to 180° with respect to one another.

10. (Currently amended) The drum flap as claimed in ~~one of the preceding claims, characterized in that~~ claim 1, wherein two outwardly protruding bearing journals ~~(6)~~ are provided on the pivot axis.

11. (Currently amended) An air-conditioning system having an air guidance housing, ~~characterized by~~ wherein a drum flap ~~(1; 101; 201; 301; 301')~~ as claimed in ~~one of claims 1 to 10~~ claim 1 arranged in the air guidance housing.

12. (Currently amended) The air-conditioning system as claimed in claim 11, ~~characterized in that~~ wherein the drum flap ~~(1; 101; 201; 301; 301')~~ serves as an air distributor flap and/or as a temperature mixing flap.